MODEL

BM-055L

High technology Even the biggest success Starts with a first step

Specifications

Item		
Capacity of Chamber		55 liter
Temperature of		50℃ ~ 60℃
Sterilizing Chamber		Preparation 3~15 minutes Stage
		Sterilization 30~35 minutes Stage
		Exhaustion & 4~25 minutes drying
Sterilant		50% hydrogen peroxide
Vacuum range		760torr~0.5torr
High voltage transformer (Plasma)	Input voltage	220V/AC 60Hz
	Output voltage	15Kvp 20Khz
Service voltage		Input : 230V~ ,50/60Hz, Single phase
Chamber Door		Sliding Door (Single)
Power consumption		2KW
Dimensions	Width	558mm
	Height	815mm
	Length	882mm
	Weight	190kg

- Cryo-prober
- Dopplers
- Electrocautery instruments
- Defibrillator paddles
- Endoscopic instruments
- Rigid endoscopes [laryngoscope & blade, arthroscopes, laparoscopes & Trocar cannula and Trocar sheaths, resectoscope and sheaths, etc]
- Flexible endcoscopes [bronchoscopes, hysteroscopes, choledochoscpers, ureteroscoprs, cystoscopes, etc.]
- Esophageal dilators
- Fiberoptic light, cables
- Laser handpieces, fibers, accessories
- Shaver handpieces / Pigmentation handpieces
- Metal instrumensts.
- Ophthalmic lenses (Diagnostic, Magnifying)
- Patient lead cable
- Radiation therapy equipment
- Surgical power equipment and batteries (Power drills)
- Ultrasound probes • Video cameras and couplers
- Medical tools designated by EcoStar-G which are within the range of sterilizing items

BeyondMedi Co., Ltd.
#401HanshinIT Tower 2Cha,Gasan-dong, Geumcheon-gu, Seoul, Korea. 153-712
Tel.+82. 2. 2025. 3060, Fax. +82. 2. 2025. 3061

GMP CE 0120

Low Temperatur e Plasma Sterilizer

High technology Even the biggest success Starts with a first step

BEYOND MEDI